

# WEIGH-TRONIX



▲  
*LCD version*

*LED version* ►

Quick Check, the new Model QC3265 Checkweigher from Weigh-Tronix, combines rugged stainless steel construction with the proven accuracy of Weigh Bar® weight sensors.



## QC3265 Checkweigher Medium Capacity

# Quick Check – Medium Capacity Model QC3265 Checkweigher

## Features and benefits

---

**NEMA 4 stainless steel display**—Quick Check is washdown safe and built for tough environments.

**Two display modes**—Quick Check operates in Weighing Mode with a simple weight display or in Checkweighing Mode with added LEDs for Over, Under, and Accept.

**Simple setup**—A single keystroke accomplishes most of the setup functions. Change target values, over and under tolerances, even units of measure in seconds.

**Simple operation**—Uncluttered display matches the Quick Check's no-nonsense operation. Just three control keys mean short training time and minimal opportunity for human error.

**Five units of measure**—Select to read in pound, ounces, kilograms, grams or pounds/ounces for added versatility.

**Single Weigh Bar® design**—No moving parts for low maintenance. Proven resistance to washdown. Suitable for food processing environments.

## Options

---

- 230 VAC 50/60 Hz power
- Built-in 30-hour battery and charger (LCD version only)
- RS-232 or RS-485 interface board
- Remote display and base (includes wall-mount bracket)

## Specifications

---

### Capacities and increments

Pounds	Ounces	Kilograms	Grams
100 x 0.02	1600 x 0.5	45 x 0.01	45,000 x 10
100 x 0.05	1600 x 0.2	45 x 0.02	45,000 x 20
200 x 0.05	3200 x 1.0	90 x 0.02	90,000 x 20
200 x 0.1	3200 x 0.5	90 x 0.05	90,000 x 50

### Overall dimensions

100-lb scales: 20" W x 28.58" D x 35" H  
(50.8 cm x 67.46 cm x 88.9 cm)  
200-lb scales: 24" W x 30.56" D x 35" H  
(60.96 cm x 77.62 cm x 88.9 cm)

### Weighing surface dimensions

100-lb scales: 20" x 20" (50.8 cm X 50.8 cm)  
200-lb scales: 24" X 24" (60.96 cm X 60.96 cm)

### Display:

LCD – 7-segment, 6-digit, 0.7" high  
LED – 7-segment, 6-digit, 0.6" high  
8 annunciators for Over, Accept, Under, lb, kg, oz, g, lb/oz and Center Zero

### Controls:

TARGET—Enters target weight  
UNITS—Changes enabled units of measure  
ZERO—Zero balances the scale

**Overload protection:** 150% of scale capacity

**Corner load:** 100% of scale capacity

### Construction:

Stainless steel, NEMA 4X electronics enclosure  
Stainless steel scale shroud and understructure  
Plated and encapsulated Weigh Bar®

### Environment:

14° to 104°F (-10° to 40°C) Water washdown

**Display-to-loadcell cable length:** 10 feet

### Power:

Standard: 115 VAC, ±10%  
50/60 Hz, 10 watts max  
Power cord length, 6 feet (1.8 meters)

**Agencies:** USDA approval, NTEP approval, UL

**Warranty:** Two-year limited warranty applies

### Weigh-Tronix

1000 Armstrong Dr.  
Fairmont, MN 56031 USA  
Telephone: 507-238-4461  
Facsimile: 507-238-4195  
e-mail: industrial@weigh-tronix.com  
www.weigh-tronix.com

### Weigh-Tronix Canada, ULC

217 Brunswick Blvd.  
Pointe Claire, QC H9R 4R7 Canada  
Telephone: 514-695-0380  
Facsimile: 514-695-6820



**WEIGH-TRONIX**

Weighing Products & Systems